



Sequoia Maintenance

The following wax free maintenance program provides a natural, low-luster appearance and a savings in labor and chemical costs when compared with conventional cleaning and floor waxing systems. If preferred, Sequoia can be successfully maintained using conventional acrylic floor finish.

Safety Precautions

- When performing any wet maintenance, always use wet floor signs and caution tape.
- Refer to each product's MSDS for use of personal protective equipment.



Newly Installed Floor Care

- Keep all foot traffic off the new floor for 12 hours.
- Keep furniture, fixtures and rolling traffic off the new floor for 48 hours.
- Use plywood or other boards when moving heavy objects across the floor.
- Remove adhesive residue with a clean white cloth dampened with mineral spirits. Do not use AFTA.
- Lightly damp mop the floor as needed.
- Wait 72 hours (3 days) before wet washing and scrubbing the new floor. This will allow the adhesive to fully cure.

Routine Maintenance

- Sweep or dust mop to remove dirt and grit. Do not use treated dust mops.
- Add neutral pH cleaner to cool water following the manufacturer's instructions.
- Rinse the mop in clean water after each mopping pass to remove picked up soil.

Periodic Deep Cleaning

- Sweep or dust mop the floor to remove dirt and grit. Do not use treated dust mops.
- Add neutral pH cleaner to cool water following the manufacturer's instructions.
- Scrub with a 175-rpm machine or auto scrubber. Use a **red pad**. Always wet the pad before use. **Never use a black or a build-up removal pad.**
- Remove the solution with a wet-dry vacuum or auto scrubber until the floor is dry and free of residue.
- Rinse the floor with clean water. Repeat the rinse process as necessary to remove all haze and residue.

Preventative Floor Care

- Proper matting system is recommended. Mats should be appropriate for soil load and weather conditions. Use mats with a non-staining backing.
- Floor protectors should be used on all furniture legs. The surface area of the floor glide should be no less than 1 inch in diameter.
- Protect the floor from direct sunlight.

Recommended Maintenance Products

- For a list of recommended maintenance products, please refer to our [Maintenance Product Guide](#) for CERES Natural Floors.

Contact Information

For additional information, please call 1-888-377-8801
Email: support@ceresnaturalfloors.com
www.ceresnaturalfloors.com

