

Fire

ASTM E648 Critical Radiant Flux	Passes
------------------------------------	--------

Test Performance

ASTM F 1303 Standard Spec for Sheet Vinyl Floor Covering with Backing	Meets or Exceeds Requirements
ASTM F 925 Chemical Resistance	Passes
ASTM F 970 Static Load Limit	Passes
ASTM D 2047 Static Coefficient of Friction	≥0.8 ADA Compliant (wet & dry)
ASTM F 137 Flexibility	Passes
ASTM F 1514 Resistance to Heat	Passes
ASTM F 1515 Resistance to Light	Passes
ASTM F 1914 Residual Indentation	Passes
CA 01350 VOC Emissions	Passes

Product Characteristics

Standard Spec	ASTM F 1303
Classification	Type II
Backing Class	Class B
Nominal Dimensions	6' Wide x 66' Long (1820 mm x 20 m)
Roll Size	44 sq yards
Overall Thickness	2.5mm (0.10")

Warranty

Takiron Pathways is covered by a limited 5-year warranty.
Visit our website, www.cbcflooring.com for complete details.

USGBC-LEED Credits

Materials & Resources

Indoor Environmental Quality

Product	MR Credit 1.2: Building Reuse	MR Credit 2: Construction Waste Management	MR Credit 3.1: Material Reuse	Recycled Content Pre-Consumer	Recycled Content Post-Consumer	MR Credit 4: Recycled Content Contribution (Sum of post-consumer + 1/2 pre-consumer)	IEQ Credit 4.1: Low Emitting Materials - Adhesives	IEQ Credit 4.3: Low Emitting Materials - Flooring Systems
Pathways	✓	✓	✓	10.2%	11%	16.1%	✓	✓

(✓) Based on the 2009 LEED rating system and the overall scope of your project Mature Sheet may contribute to your LEED scorecard.

CBC Flooring is ISO 9001 and 14001 certified