

Fire

ASTM E648 Critical Radiant Flux	Class 1 (>0.45/sq cm)
ASTM E 662 Smoke Generation	<450 Flaming & Non Flaming

Test Performance

ASTM F 1066 Standard Spec for Vinyl Composition Floor Tile	Meets or Exceeds Requirements
ASTM F 925 Chemical Resistance	Passes
ASTM F 970 (modified) Static Load Limit	1,000 PSI
ASTM C 1028 Static Coefficient of Friction	≥0.6 ADA Compliant
ASTM F 2199 Dimensional Stability	Passes
ASTM F 1265 Resistance to Impact	Passes
ASTM F 1304 Deflection of Tile	Passes
ASTM F 1515 Resistance to Light	Passes
CA 01350 VOC Emissions	Passes FloorScore Certified FS-03026

Product Characteristics

Standard Spec	ASTM 1066
Classification	Class II
Nominal Dimensions	17.7" x 17.7" (450mm x 450mm)
Overall Thickness	3.0mm (0.120")
Packaging	30.5 SF per Carton (14 pcs)

Warranty

TOLI Strataline is covered by a limited 10-year warranty.
Visit our website, www.cbcflooring.com for complete details.

USGBC-LEED Credits

Materials & Resources

Indoor Environmental Quality

Product	MR Credit 1.2: Building Reuse	MR Credit 2: Construction Waste Management	MR Credit 3.1: Material Reuse	Recycled Content Pre-Consumer	Recycled Content Post-Consumer	MR Credit 4: Recycled Content Contribution (Sum of post-consumer + 1/2 pre-consumer)	IEQ Credit 4.1: Low Emitting Materials - Adhesives	IEQ Credit 4.3: Low Emitting Materials - Flooring Systems
Strataline	✓	✓	✓	28%	4.8%	18.8%	✓	✓

(✓) Based on the 2009 LEED rating system and the overall scope of your project Mature Sheet may contribute to your LEED scorecard.

CBC Flooring is ISO 9001 and 14001 certified