

## Fire

ASTM E648 Critical Radiant Flux	Class 1 (>0.45/sq cm)
ASTM E 662 Smoke Generation	<450

## Test Performance

ASTM F 1700 Standard Spec for Solid Vinyl Floor	Meets or Exceeds Requirements
ASTM F 925 Chemical Resistance	Passes
ASTM F 970 (modified) Static Load Limit	2,500 PSI
ASTM C 1028 Static Coefficient of Friction	≥0.6 ADA Compliant
ASTM F 137 Flexibility	Passes
ASTM F 1514 Resistance to Heat	Passes
ASTM F 1515 Resistance to Light	Passes
CA 01350 VOC Emissions	Exceeds Requirements

## Product Characteristics

Standard Spec	ASTM F 1700
Classification	Class III Type A & B
Nominal Dimensions / Packaging	12" x 24" (305mm x 610mm) 20 pcs/ctn (20 sf/ctn)  18" x 18" (457mm x 457mm) 20 pcs/ctn (45 sf/ctn)  24" x 24" (610mm x 610mm) 8 pcs/ctn (32 sf/ctn)
Overall Thickness	3.0mm (0.12")
Wear Layer Thickness	0.7 mm (0.028")

## Warranty

Halo Stones & More is covered by a limited 15-year warranty. Visit our website, [www.cbcflooring.com](http://www.cbcflooring.com) for complete details.

## USGBC-LEED Credits

### Materials & Resources

### Indoor Environmental Quality

Product	MR Credit 1.2: Building Reuse	MR Credit 2: Construction Waste Management	MR Credit 3.1: Material Reuse	Recycled Content Pre-Consumer	Recycled Content Post-Consumer	MR Credit 4: Recycled Content Contribution (Sum of post-consumer + 1/2 pre-consumer)	IEQ Credit 4.1: Low Emitting Materials - Adhesives	IEQ Credit 4.3: Low Emitting Materials - Flooring Systems
<b>Stones &amp; More</b>	✓	✓	✓	13%	0%	6.5%	✓	✓

(✓) Based on the 2009 LEED rating system and the overall scope of your project Mature Sheet may contribute to your LEED scorecard.

CBC Flooring is ISO 9001 and 14001 certified