

Fire

ASTM E648 Critical Radiant Flux	Class 1
------------------------------------	---------

Test Performance

ASTM D 2047 Static Coefficient of Friction	≥0.6 ADA Compliant
ASTM D 3389 Abrasion Resistance	<0.13 mg/cycle
ASTM F 1514 Resistance to Heat	<1
ASTM F 1515 Resistance to Light	<1
ASTM F 925 Chemical Resistance	No effects
ASTM F 970 Static Load Limit	>600 PSI
CA 01350 VOC Emissions	Passes

Product Characteristics

Standard Spec	ASTM F 1303
Classification	Type TV
Packaging	4' (1220mm) Length 7 pcs/ctn
	6' (1828mm) Length 5 pcs/ctn
Tread Thickness	2.5mm (0.098")
Tread Depth	500mm (19.69")
Nose Height	40mm (1.57")
Nosing Thickness	4mm (0.157")

Warranty

Takiron Stair Treads are covered by a limited 5-year warranty. Visit our website, www.cbcflooring.com for complete details.

USGBC-LEED Credits

Materials & Resources

Indoor Environmental Quality

Product	MR Credit 1.2: Building Reuse	MR Credit 2: Construction Waste Management	Recycled Content Pre-Consumer	Recycled Content Post-Consumer	MR Credit 4: Recycled Content Contribution (Sum of post-consumer + 1/2 pre-consumer)	IEQ Credit 4.1: Low Emitting Materials - Adhesives	IEQ Credit 4.3: Low Emitting Materials - Flooring Systems
Stair Treads	✓	✓	3.8%	4.1%	6.0%	✓	✓

✓ Based on the 2009 LEED rating system and the overall scope of your project Mature Sheet may contribute to your LEED scorecard.

CBC Flooring is ISO 9001 and 14001 certified