

## Fire

ASTM E648 Critical Radiant Flux	Class 1 Passes (>0.45 watts per cm <sup>2</sup> )
ASTM E 662 Smoke Generation	<450

## Test Performance

ASTM F 1700 Standard Spec for Solid Vinyl Floor	Meets or Exceeds Requirements
ASTM F 925 Chemical Resistance	Passes
ASTM F 970 (modified) Static Load Limit	750 PSI
ASTM D 2047 Static Coefficient of Friction	0.6
ASTM F 137 Flexibility	Passes
ASTM F 1514 Resistance to Heat	Passes
ASTM F 1515 Resistance to Light	Passes
CA 01350 VOC Emissions	Passes FloorScore Certified FS-05645 HPD currently available

## Product Characteristics

Standard Spec	ASTM 1700
Classification	Class III Type A & B
Nominal Dimensions / Packaging	4" x 36" (102mm x 914mm) 36 pcs/ctn (36 sf/ctn)  7" x 48" (178mm x 1220mm) 15 pcs/ctn (35 sf/ctn)
Overall Thickness	2.5mm (0.10")
Wear Layer Thickness	0.5mm (0.020")

## Warranty

TOLI Kareina Asento is covered by a limited 10-year warranty. Visit our website, [www.cbcflooring.com](http://www.cbcflooring.com) for complete details.

CBC Flooring is ISO 9001 and 14001 certified